

Multi Function Telephone

RD-Telephone

Overview

Multi Function Telephone{RD(Ring Down)-TEL} is designed under the Military Specifications. And It operates with the PBX for transferring voice signal.

Features

- CB(Common Battery), LB(Local Battery), RD(Ring Down) Mode
- Receiving voice volume control function
- Buzzer volume control function
- Water Proof design
- Interrupt-call function for priority call(RCS)



Specification

- Electrical
 - Frequency Range : 300~3,400Hz
 - Transmission Power : -5dBm
 - Receive sensitivity : 105dB(0dBm, 1KHz)
 - Ring Signaling Acoustic Level : 70dB SPL
- Transmit Distance
 - 8Km(CB), 16Km(LB), 32Km(RD)
- Temperature
 - -35°C ~+55°C (Operating)
 - -55°C ~+71°C (Storage)
- Environmental Specification
 - MIL-STD-810F
- Dimension & Weigh
 - 123(W)mm X 210(L)mm X 80(H)mm
 - 1.5Kg blow

Applications

RD-TEL(CB:8Km, LB:16Km)

RD-TEL(CB:8Km, LB:16Km)



전용회선



RD-TEL(RD:32Km)

PBX

PBX

RD-TEL(RD:32Km)

선로



WooriByul

■ Address : 89, Hwanggeum 1-ro, Yangchon-eup,
Gimpo-si, Gyeonggi-do, Korea

■ TEL : +82-31-980-7500 / FAX : +82-31-985-6222

■ <http://www.wooribyul.co.kr>